

# Product Data Sheet

## SORB®XT Stripper

Article	SORB®XT Stripper 20 kg
Article no.	100825
Dimensions (mm)	330 x 330 x 328
Weight (kg)	20,00



¡Scan me!

### Product Information:

#### Product description

- the SORB®XT Stripper was specially developed for the removal of surface coatings. The SORB®XT Stripper is ready to use and allows the effortless removal of paint coatings as well as EP, PU, PVC, acrylate and styrene acrylate coatings

#### Storage

- the tightly closed original containers can be stored for at least 1 year at temperatures between + 5 °C and + 30 °C in a dry environment

#### Application

- SORB®XT Stripper is applied undiluted to the surface coating to be removed
- depending on the spraying technique, the material can be diluted with water for better workability
- after applying the SORB®XT Stripper, the surfaces should be covered with foil. Suspension prevents the remover from drying out and intensifies the removal of the old coating
- the exposure time depends on the ambient temperature and the surface coating to be removed as well as its layer thickness

#### After the application

- the coatings are either completely destroyed or softened to such an extent that they can be removed mechanically
- after a sufficient exposure time, the softened old coating can be removed by means of a spatula or high-pressure cleaner
- in the case of contaminated coatings or environmentally hazardous substances in the old coating, the removed residues must be collected and disposed of
- the legal requirements must be complied with during disposal

#### Properties

- pH-neutral
- stable, machine-processed paint stripper
- CHC-free paint stripper
- effective against EP, PU, PVC, acrylate, styrene acrylate
- good processing properties, ready for use
- low odor
- one-component